

268  
HANDHELD CASES

292  
UNIVERSAL  
ENCLOSURES

318  
HEAVY DUTY  
AND ELECTRICAL  
ENCLOSURES

342  
DESKTOP AND  
INSTRUMENT  
CASES

348  
DEVELOPMENT  
BOARD  
ENCLOSURES

367  
VERSATILE IOT  
AND SENSOR  
ENCLOSURES

370  
CUSTOM SIZED  
ENCLOSURES

PLASTIC ENCLOSURES

# Room sensor enclosures



## Product overview



A range of versatile wall mountable enclosures, available in two body types, three sizes and three colours. The vented housing allows airflow, making them ideal for thermostats, environmental sensing and IoT applications. The solid housing lends itself to wall mount controls and smart applications such as lighting, security or network modules.

- Moulded in recyclable ABS UL94-V0
- Front and back clip together construction (tool required for disassembly once mounted)
- Internal PCB mount pillars moulded into the front and back sections of the housing (Pi A+ fits base of CBR202, no PCB mounts in back of CBR203)
- Internal clips moulded into fronts for snap-in PCB (Arduino fits CBR202 and Thunder Sense fits CBR203)
- Recessed front face for overlay
- Recesses in rear face for additional labelling (CRBS01 and CBR202)
- Solid and vented versions available
- Rear knockout for cable entry (20mm diameter)
- Multiple mounting options, including single gang UK-plug back box (CBRS01)
- Sizes to house standard batteries: PP3-9V & AA in CBR201 & CBR202, CR3032 Coin-Cell in CBR203
- Three colour options: white RAL9003, light grey RAL7047 and black RAL9005
- Manufactured in the UK



SPECIFICATION	
Materials	ABS UL94-V0
Operating temperature	-10°C to + 70°C
Standard unit includes	Enclosure lid Enclosure base

WHITE	BLACK	GREY	SIZE	STYLE	LENGTH	WIDTH	HEIGHT
CBRS01SWH	CBRS01SBK	CBRS01SGY	1	Solid	86mm	86mm	25.5mm
CBRS01VWH	CBRS01VBK	CBRS01VGY	1	Vented	86mm	86mm	25.5mm
CBRS02SWH	CBRS02SBK	CBRS02SGY	2	Solid	74mm	74mm	25.5mm
CBRS02VWH	CBRS02VBK	CBRS02VGY	2	Vented	74mm	74mm	25.5mm
CBRS03SWH	CBRS03SBK	CBRS03SGY	3	Solid	51mm	51mm	25.5mm
CBRS03VWH	CBRS03VBK	CBRS03VGY	3	Vented	51mm	51mm	25.5mm



## KEY FEATURES

Smart electronics enclosure | No screws needed | Easy wall mounting

